

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流+25 ℃(uA)	漏电流+85 ℃(uA)	漏电流 +125℃ (uA)	损耗角正切 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
6.3 Volt 额定电压 +85℃时 (4 Volt 额定电压 +125℃时)												
22	CA351-6.3V22uF(*)A	T3510A226(*)006(**)	(*)	6.3V22uF	A	1	6	6		6	6	6
33	CA351-6.3V33uF(*)A	T3510A336(*)006(**)	(*)	6.3V33uF	A	1	6	6		8	8	8
47	CA351-6.3V47uF(*)A	T3510A476(*)006(**)	(*)	6.3V47uF	A	1	6	6		10	10	10
68	CA351-6.3V68uF(*)A	T3510A686(*)006(**)	(*)	6.3V68uF	A	1	6	6		15	15	15
100	CA351-6.3V100uF(*)B	T3510B107(*)006(**)	(*)	6.3V100uF	B	1	6	6		15	15	15
150	CA351-6.3V150uF(*)B	T3510B157(*)006(**)	(*)	6.3V150uF	B	1	6	6		20	20	20
220	CA351-6.3V220uF(*)C	T3510C227(*)006(**)	(*)	6.3V220uF	C	1.1	8.3	8.3		20	20	20
270	CA351-6.3V270uF(*)C	T3510C277(*)006(**)	(*)	6.3V270uF	C	1.4	10.2	10.2		30	30	30
330	CA351-6.3V330uF(*)C	T3510C337(*)006(**)	(*)	6.3V330uF	C	1.7	12.5	12.5		30	30	30
470	CA351-6.3V470uF(*)D	T3510D477(*)006(**)	(*)	6.3V470uF	D	2.4	17.8	17.8		40	40	40
560	CA351-6.3V560uF(*)D	T3510D567(*)006(**)	(*)	6.3V560uF	D	2.8	21.2	21.2		45	45	45
680	CA351-6.3V680uF(*)D	T3510D687(*)006(**)	(*)	6.3V680uF	D	3.4	25.7	25.7		45	45	45
820	CA351-6.3V820uF(*)E	T3510E827(*)006(**)	(*)	6.3V820uF	E	4.1	31.0	31.0		50	50	50
1000	CA351-6.3V1000uF(*)E	T3510E108(*)006(**)	(*)	6.3V1000uF	E	5.0	37.8	37.8		55	55	55
1200	CA351-6.3V1200uF(*)F	T3510F128(*)006(**)	(*)	6.3V1200uF	F	6.0	45.4	45.4		55	55	55
1500	CA351-6.3V1500uF(*)G	T3510G158(*)006(**)	(*)	6.3V1500uF	G	7.6	56.7	56.7		70	70	70
2200	CA351-6.3V2200uF(*)H	T3510H228(*)006(**)	(*)	6.3V2200uF	H	11.1	83.2	83.2		80	80	80
10 Volt 额定电压 +85℃时 (6.3 Volt 额定电压 +125℃时)												
15	CA351-10V15uF(*)A	T3510A156(*)010(**)	(*)	10V15uF	A	1	6	6		6	6	6
22	CA351-10V22uF(*)A	T3510A226(*)010(**)	(*)	10V22uF	A	1	6	6		6	6	6
25	CA351-10V25uF(*)A	T3510A256(*)010(**)	(*)	10V25uF	A	1	6	6		8	8	8
33	CA351-10V33uF(*)A	T3510A336(*)010(**)	(*)	10V33uF	A	1	6	6		10	10	10
47	CA351-10V47uF(*)A	T3510A476(*)010(**)	(*)	10V47uF	A	1	6	6		10	10	10
56	CA351-10V56uF(*)A	T3510A566(*)010(**)	(*)	10V56uF	A	1	6	6		10	10	10
68	CA351-10V68uF(*)B	T3510B686(*)010(**)	(*)	10V68uF	B	1	6	6		12	12	12
100	CA351-10V100uF(*)B	T3510B107(*)010(**)	(*)	10V100uF	B	1	6.0	6.0		12	12	12
120	CA351-10V120uF(*)B	T3510B127(*)010(**)	(*)	10V120uF	B	1	7.2	7.2		18	18	18
150	CA351-10V150uF(*)C	T3510C157(*)010(**)	(*)	10V150uF	C	1.2	9.0	9.0		18	18	18
180	CA351-10V180uF(*)C	T3510C187(*)010(**)	(*)	10V180uF	C	1.4	10.8	10.8		20	20	20
220	CA351-10V220uF(*)C	T3510C227(*)010(**)	(*)	10V220uF	C	1.8	13.2	13.2		25	25	25
250	CA351-10V250uF(*)C	T3510C257(*)010(**)	(*)	10V250uF	C	2.0	15.0	15.0		30	30	30
330	CA351-10V330uF(*)D	T3510D337(*)010(**)	(*)	10V330uF	D	2.6	19.8	19.8		30	30	30
390	CA351-10V390uF(*)D	T3510D397(*)010(**)	(*)	10V390uF	D	3.1	23.4	23.4		30	30	30
470	CA351-10V470uF(*)D	T3510D477(*)010(**)	(*)	10V470uF	D	3.8	28.2	28.2		35	35	35
560	CA351-10V560uF(*)E	T3510E567(*)010(**)	(*)	10V560uF	E	4.5	33.6	33.6		40	40	40
680	CA351-10V680uF(*)E	T3510E687(*)010(**)	(*)	10V680uF	E	5.4	40.8	40.8		40	40	40
850	CA351-10V850uF(*)F	T3510F857(*)010(**)	(*)	10V850uF	F	6.8	51.0	51.0		50	50	50
1000	CA351-10V1000uF(*)F	T3510F108(*)010(**)	(*)	10V1000uF	F	8.0	60.0	60.0		50	50	50
1200	CA351-10V1200uF(*)G	T3510G128(*)010(**)	(*)	10V1200uF	G	9.6	72.0	72.0		55	55	55
1500	CA351-10V1500uF(*)H	T3510H158(*)010(**)	(*)	10V1500uF	H	12.0	90.0	90.0		55	55	55
1800	CA351-10V1800uF(*)H	T3510H188(*)010(**)	(*)	10V1800uF	H	14.4	108.0	108.0		70	70	70
2200	CA351-10V2200uF(*)H	T3510H228(*)010(**)	(*)	10V2200uF	H	17.6	132.0	132.0		80	80	80
16 Volt 额定电压 +85℃时 (10 Volt 额定电压 +125℃时)												
10	CA351-16V10uF(*)A	T3510A106(*)016(**)	(*)	16V10uF	A	1	6	6		5.7	5.7	5.7
15	CA351-16V15uF(*)A	T3510A156(*)016(**)	(*)	16V15uF	A	1	6	6		5.7	5.7	5.7
22	CA351-16V22uF(*)A	T3510A226(*)016(**)	(*)	16V22uF	A	1	6	6		6	6	6
33	CA351-16V33uF(*)A	T3510A336(*)016(**)	(*)	16V33uF	A	1	6	6		8	8	8
47	CA351-16V47uF(*)B	T3510B476(*)016(**)	(*)	16V47uF	B	1	6	6		10	10	10
68	CA351-16V68uF(*)B	T3510B686(*)016(**)	(*)	16V68uF	B	1	6.5	6.5		15	15	15
100	CA351-16V100uF(*)C	T3510C107(*)016(**)	(*)	16V100uF	C	1.3	9.6	9.6		16	16	16
120	CA351-16V120uF(*)C	T3510C127(*)016(**)	(*)	16V120uF	C	1.5	11.5	11.5		18	18	18
150	CA351-16V150uF(*)C	T3510C157(*)016(**)	(*)	16V150uF	C	1.9	14.4	14.4		18	18	18
220	CA351-16V220uF(*)D	T3510D227(*)016(**)	(*)	16V220uF	D	2.8	21.1	21.1		18	18	18
270	CA351-16V270uF(*)D	T3510D277(*)016(**)	(*)	16V270uF	D	3.5	25.9	25.9		25	25	25
330	CA351-16V330uF(*)D	T3510D337(*)016(**)	(*)	16V330uF	D	4.2	31.7	31.7		30	30	30
390	CA351-16V390uF(*)E	T3510E397(*)016(**)	(*)	16V390uF	E	5.0	37.4	37.4		35	35	35
470	CA351-16V470uF(*)E	T3510E477(*)016(**)	(*)	16V470uF	E	6.0	45.1	45.1		35	35	35
540	CA351-16V540uF(*)F	T3510F547(*)016(**)	(*)	16V540uF	F	6.9	51.8	51.8		45	45	45
680	CA351-16V680uF(*)F	T3510F687(*)016(**)	(*)	16V680uF	F	8.7	65.3	65.3		45	45	45
820	CA351-16V820uF(*)G	T3510G827(*)016(**)	(*)	16V820uF	G	10.5	78.7	78.7		55	55	55
1000	CA351-16V1000uF(*)G	T3510G108(*)016(**)	(*)	16V1000uF	G	12.8	96.0	96.0		65	65	65
1500	CA351-16V1500uF(*)H	T3510H158(*)016(**)	(*)	16V1500uF	H	19.2	144.0	144.0		70	70	70
25 Volt 额定电压 +85℃时 (16 Volt 额定电压 +125℃时)												
6.8	CA351-25V6.8uF(*)A	T3510A685(*)025(**)	(*)	25V6.8uF	A	1	6	6		4.6	4.6	4.6
10	CA351-25V10uF(*)A	T3510A106(*)025(**)	(*)	25V10uF	A	1	6	6		4.6	4.6	4.6
15	CA351-25V15uF(*)A	T3510A156(*)025(**)	(*)	25V15uF	A	1	6	6		6.5	6.5	6.5
22	CA351-25V22uF(*)A	T3510A226(*)025(**)	(*)	25V22uF	A	1	6	6		7	7	7
33	CA351-25V33uF(*)B	T3510B336(*)025(**)	(*)	25V33uF	B	1	6	6		9	9	9
47	CA351-25V47uF(*)B	T3510B476(*)025(**)	(*)	25V47uF	B	1	7.1	7.1		9	9	9
68	CA351-25V68uF(*)C	T3510C686(*)025(**)	(*)	25V68uF	C	1.4	10.2	10.2		9	9	9
100	CA351-25V100uF(*)C	T3510C107(*)025(**)	(*)	25V100uF	C	2.0	15.0	15.0		12	12	12
150	CA351-25V150uF(*)D	T3510D157(*)025(**)	(*)	25V150uF	D	3.0	22.5	22.5		14	14	14
180	CA351-25V180uF(*)D	T3510D187(*)025(**)	(*)	25V180uF	D	3.6	27.0	27.0		15	15	15

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流+25 ℃(uA)	漏电流+85 ℃(uA)	漏电流 +125℃ (uA)	损耗角正切 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
220	CA351-25V220uF(*)D	T3510D227(*)025(**)	(*)	25V220uF	D	4.4	33.0	33.0		15	15	15
270	CA351-25V270uF(*)E	T3510E277(*)025(**)	(*)	25V270uF	E	5.4	40.5	40.5		20	20	20
330	CA351-25V330uF(*)E	T3510E337(*)025(**)	(*)	25V330uF	E	6.6	49.5	49.5		20	20	20
470	CA351-25V470uF(*)F	T3510F477(*)025(**)	(*)	25V470uF	F	9.4	70.5	70.5		30	30	30
560	CA351-25V560uF(*)G	T3510G567(*)025(**)	(*)	25V560uF	G	11.2	84.0	84.0		45	45	45
680	CA351-25V680uF(*)G	T3510G687(*)025(**)	(*)	25V680uF	G	13.6	102.0	102.0		45	45	45
1000	CA351-25V1000uF(*)H	T3510H108(*)025(**)	(*)	25V1000uF	H	20.0	150.0	150.0		45	45	45
1200	CA351-25V1200uF(*)H	T3510H128(*)025(**)	(*)	25V1200uF	H	24.0	180.0	180.0		50	50	50
40 Volt 额定电压 +85℃时 (25 Volt 额定电压 +125℃时)												
4.7	CA351-40V4.7uF(*)A	T3510A475(*)040(**)	(*)	40V4.7uF	A	1	6	6		4.5	4.5	4.5
6.8	CA351-40V6.8uF(*)A	T3510A685(*)040(**)	(*)	40V6.8uF	A	1	6	6		4.5	4.5	4.5
8	CA351-40V8uF(*)A	T3510A805(*)040(**)	(*)	40V8uF	A	1	6	6		4.5	4.5	4.5
10	CA351-40V10uF(*)A	T3510A106(*)040(**)	(*)	40V10uF	A	1	6	6		4.5	4.5	4.5
15	CA351-40V15uF(*)A	T3510A156(*)040(**)	(*)	40V15uF	A	1	6	6		7	7	7
22	CA351-40V22uF(*)B	T3510B226(*)040(**)	(*)	40V22uF	B	1	6	6		7	7	7
33	CA351-40V33uF(*)B	T3510B336(*)040(**)	(*)	40V33uF	B	1.1	7.9	7.9		8	8	8
40	CA351-40V40uF(*)C	T3510C406(*)040(**)	(*)	40V40uF	C	1.3	9.6	9.6		8	8	8
47	CA351-40V47uF(*)C	T3510C476(*)040(**)	(*)	40V47uF	C	1.5	11.3	11.3		8	8	8
56	CA351-40V56uF(*)C	T3510C566(*)040(**)	(*)	40V56uF	C	1.8	13.4	13.4		10	10	10
68	CA351-40V68uF(*)C	T3510C686(*)040(**)	(*)	40V68uF	C	2.2	16.3	16.3		10	10	10
100	CA351-40V100uF(*)D	T3510D107(*)040(**)	(*)	40V100uF	D	3.2	24.0	24.0		12	12	12
150	CA351-40V150uF(*)E	T3510E157(*)040(**)	(*)	40V150uF	E	4.8	36.0	36.0		15	15	15
220	CA351-40V220uF(*)F	T3510F227(*)040(**)	(*)	40V220uF	F	7.0	52.8	52.8		20	20	20
330	CA351-40V330uF(*)G	T3510G337(*)040(**)	(*)	40V330uF	G	10.6	79.2	79.2		25	25	25
470	CA351-40V470uF(*)G	T3510G477(*)040(**)	(*)	40V470uF	G	15.0	112.8	112.8		30	30	30
560	CA351-40V560uF(*)H	T3510H567(*)040(**)	(*)	40V560uF	H	17.9	134.4	134.4		35	35	35
680	CA351-40V680uF(*)H	T3510H687(*)040(**)	(*)	40V680uF	H	21.8	163.2	163.2		40	40	40
1000	CA351-40V1000uF(*)H	T3510H108(*)040(**)	(*)	40V1000uF	H	32.0	240.0	240.0		50	50	50
50 Volt 额定电压 +85℃时 (30 Volt 额定电压 +125℃时)												
5	CA351-50V5uF(*)A	T3510A505(*)050(**)	(*)	50V5uF	A	1	6	6		5	5	5
6.8	CA351-50V6.8uF(*)A	T3510A685(*)050(**)	(*)	50V6.8uF	A	1	6	6		5	5	5
10	CA351-50V10uF(*)A	T3510A106(*)050(**)	(*)	50V10uF	A	1	6	6		5	5	5
15	CA351-50V15uF(*)B	T3510B156(*)050(**)	(*)	50V15uF	B	1	6	6		6	6	6
22	CA351-50V22uF(*)B	T3510B226(*)050(**)	(*)	50V22uF	B	1	6.6	6.6		8	8	8
25	CA351-50V25uF(*)C	T3510C256(*)050(**)	(*)	50V25uF	C	1.0	7.5	7.5		10	10	10
33	CA351-50V33uF(*)C	T3510C336(*)050(**)	(*)	50V33uF	C	1.3	9.9	9.9		12	12	12
47	CA351-50V47uF(*)C	T3510C476(*)050(**)	(*)	50V47uF	C	1.9	14.1	14.1		15	15	15
60	CA351-50V60uF(*)D	T3510D606(*)050(**)	(*)	50V60uF	D	2.4	18.0	18.0		15	15	15
68	CA351-50V68uF(*)D	T3510D686(*)050(**)	(*)	50V68uF	D	2.7	20.4	20.4		20	20	20
82	CA351-50V82uF(*)D	T3510D826(*)050(**)	(*)	50V82uF	D	3.3	24.6	24.6		20	20	20
100	CA351-50V100uF(*)E	T3510E107(*)050(**)	(*)	50V100uF	E	4.0	30.0	30.0		20	20	20
120	CA351-50V120uF(*)E	T3510E127(*)050(**)	(*)	50V120uF	E	4.8	36.0	36.0		22	22	22
150	CA351-50V150uF(*)F	T3510F157(*)050(**)	(*)	50V150uF	F	6.0	45.0	45.0		25	25	25
160	CA351-50V160uF(*)F	T3510F167(*)050(**)	(*)	50V160uF	F	6.4	48.0	48.0		25	25	25
220	CA351-50V220uF(*)F	T3510F227(*)050(**)	(*)	50V220uF	F	8.8	66.0	66.0		30	30	30
270	CA351-50V270uF(*)F	T3510F277(*)050(**)	(*)	50V270uF	F	10.8	81.0	81.0		37	37	37
330	CA351-50V330uF(*)G	T3510G337(*)050(**)	(*)	50V330uF	G	13.2	99.0	99.0		38	38	38
470	CA351-50V470uF(*)H	T3510H477(*)050(**)	(*)	50V470uF	H	18.8	141.0	141.0		40	40	40
680	CA351-50V680uF(*)H	T3510H687(*)050(**)	(*)	50V680uF	H	27.2	204.0	204.0		45	45	45
63 Volt 额定电压 +85℃时 (40 Volt 额定电压 +125℃时)												
2.2	CA351-63V2.2uF(*)A	T3510A225(*)063(**)	(*)	63V2.2uF	A	1	6	6		4	4	4
3.3	CA351-63V3.3uF(*)A	T3510A335(*)063(**)	(*)	63V3.3uF	A	1	6	6		4.5	4.5	4.5
4	CA351-63V4uF(*)A	T3510A405(*)063(**)	(*)	63V4uF	A	1	6	6		5	5	5
4.7	CA351-63V4.7uF(*)A	T3510A475(*)063(**)	(*)	63V4.7uF	A	1	6	6		5	5	5
6.8	CA351-63V6.8uF(*)A	T3510A685(*)063(**)	(*)	63V6.8uF	A	1	6	6		5	5	5
8.2	CA351-63V8.2uF(*)A	T3510A825(*)063(**)	(*)	63V8.2uF	A	1	6	6		6	6	6
10	CA351-63V10uF(*)B	T3510B106(*)063(**)	(*)	63V10uF	B	1	6	6		6	6	6
15	CA351-63V15uF(*)B	T3510B156(*)063(**)	(*)	63V15uF	B	1	6	6		6	6	6
22	CA351-63V22uF(*)C	T3510C226(*)063(**)	(*)	63V22uF	C	1.1	8.3	8.3		8	8	8
27	CA351-63V27uF(*)C	T3510C276(*)063(**)	(*)	63V27uF	C	1.4	10.2	10.2		8	8	8
33	CA351-63V33uF(*)C	T3510C336(*)063(**)	(*)	63V33uF	C	1.7	12.5	12.5		8	8	8
39	CA351-63V39uF(*)C	T3510C396(*)063(**)	(*)	63V39uF	C	2.0	14.7	14.7		8	8	8
47	CA351-63V47uF(*)D	T3510D476(*)063(**)	(*)	63V47uF	D	2.4	17.8	17.8		8	8	8
68	CA351-63V68uF(*)D	T3510D686(*)063(**)	(*)	63V68uF	D	3.4	25.7	25.7		10	10	10
100	CA351-63V100uF(*)E	T3510E107(*)063(**)	(*)	63V100uF	E	5.0	37.8	37.8		12	12	12
150	CA351-63V150uF(*)F	T3510F157(*)063(**)	(*)	63V150uF	F	7.6	56.7	56.7		15	15	15
220	CA351-63V220uF(*)G	T3510G227(*)063(**)	(*)	63V220uF	G	11.1	83.2	83.2		20	20	20
270	CA351-63V270uF(*)H	T3510H277(*)063(**)	(*)	63V270uF	H	13.6	102.1	102.1		25	25	25
330	CA351-63V330uF(*)H	T3510H337(*)063(**)	(*)	63V330uF	H	16.6	124.7	124.7		30	30	30
470	CA351-63V470uF(*)H	T3510H477(*)063(**)	(*)	63V470uF	H	23.7	177.7	177.7		30	30	30
75 Volt 额定电压 +85℃时 (50 Volt 额定电压 +125℃时)												
3.5	CA351-75V3.5uF(*)A	T3510A355(*)075(**)	(*)	75V3.5uF	A	1	6	6		4.5	4.5	4.5
4.7	CA351-75V4.7uF(*)A	T3510A475(*)075(**)	(*)	75V4.7uF	A	1	6	6		4.5	4.5	4.5
6.8	CA351-75V6.8uF(*)A	T3510A685(*)075(**)	(*)	75V6.8uF	A	1	6	6		4.7	4.7	4.7

容量 (uF)	聚电料号	ADMAT料号	容量 偏差	规格	壳号	漏电流+25 ℃(uA)	漏电流+85 ℃(uA)	漏电流 +125℃ (uA)	损耗角正切 55℃ 120Hz(%)	损耗角正切 +25℃ 120Hz(%)	损耗角正切 +85℃ 120Hz(%)	损耗角正切 +125℃ 120Hz(%)
10	CA351-75V10uF(*)B	T3510B106(*)075(**)	(*)	75V10uF	B	1	6	6		6	6	6
15	CA351-75V15uF(*)B	T3510B156(*)075(**)	(*)	75V15uF	B	1	6.8	6.8		6	6	6
22	CA351-75V22uF(*)C	T3510C226(*)075(**)	(*)	75V22uF	C	1.3	9.9	9.9		8	8	8
33	CA351-75V33uF(*)C	T3510C336(*)075(**)	(*)	75V33uF	C	2.0	14.9	14.9		8	8	8
40	CA351-75V40uF(*)D	T3510D406(*)075(**)	(*)	75V40uF	D	2.4	18.0	18.0		8	8	8
47	CA351-75V47uF(*)D	T3510D476(*)075(**)	(*)	75V47uF	D	2.8	21.2	21.2		8	8	8
56	CA351-75V56uF(*)D	T3510D566(*)075(**)	(*)	75V56uF	D	3.4	25.2	25.2		10	10	10
68	CA351-75V68uF(*)E	T3510E686(*)075(**)	(*)	75V68uF	E	4.1	30.6	30.6		10	10	10
82	CA351-75V82uF(*)E	T3510E826(*)075(**)	(*)	75V82uF	E	4.9	36.9	36.9		12	12	12
100	CA351-75V100uF(*)F	T3510F107(*)075(**)	(*)	75V100uF	F	6.0	45.0	45.0		12	12	12
110	CA351-75V110uF(*)F	T3510F117(*)075(**)	(*)	75V110uF	F	6.6	49.5	49.5		15	15	15
150	CA351-75V150uF(*)G	T3510G157(*)075(**)	(*)	75V150uF	G	9.0	67.5	67.5		15	15	15
180	CA351-75V180uF(*)G	T3510G187(*)075(**)	(*)	75V180uF	G	10.8	81.0	81.0		20	20	20
220	CA351-75V220uF(*)H	T3510H227(*)075(**)	(*)	75V220uF	H	13.2	99.0	99.0		25	25	25
330	CA351-75V330uF(*)H	T3510H337(*)075(**)	(*)	75V330uF	H	19.8	148.5	148.5		30	30	30
100 Volt 额定电压 +85℃时 (63 Volt 额定电压 +125℃时)												
1.5	CA351-100V1.5uF(*)A	T3510A155(*)100(**)	(*)	100V1.5uF	A	1	6	6		5	5	5
2.2	CA351-100V2.2uF(*)A	T3510A225(*)100(**)	(*)	100V2.2uF	A	1	6	6		5	5	5
3.3	CA351-100V3.3uF(*)A	T3510A335(*)100(**)	(*)	100V3.3uF	A	1	6	6		6	6	6
4.7	CA351-100V4.7uF(*)A	T3510A475(*)100(**)	(*)	100V4.7uF	A	1	6	6		6	6	6
6.8	CA351-100V6.8uF(*)B	T3510B685(*)100(**)	(*)	100V6.8uF	B	1	6	6		7	7	7
10	CA351-100V10uF(*)B	T3510B106(*)100(**)	(*)	100V10uF	B	1	6.0	6.0		8	8	8
15	CA351-100V15uF(*)C	T3510C156(*)100(**)	(*)	100V15uF	C	1.2	9.0	9.0		10	10	10
22	CA351-100V22uF(*)C	T3510C226(*)100(**)	(*)	100V22uF	C	1.8	13.2	13.2		10	10	10
33	CA351-100V33uF(*)D	T3510D336(*)100(**)	(*)	100V33uF	D	2.6	19.8	19.8		10	10	10
39	CA351-100V39uF(*)E	T3510E396(*)100(**)	(*)	100V39uF	E	3.1	23.4	23.4		10	10	10
47	CA351-100V47uF(*)E	T3510E476(*)100(**)	(*)	100V47uF	E	3.8	28.2	28.2		10	10	10
68	CA351-100V68uF(*)F	T3510F686(*)100(**)	(*)	100V68uF	F	5.4	40.8	40.8		10	10	10
86	CA351-100V86uF(*)F	T3510F866(*)100(**)	(*)	100V86uF	F	6.9	51.6	51.6		10	10	10
100	CA351-100V100uF(*)G	T3510G107(*)100(**)	(*)	100V100uF	G	8.0	60.0	60.0		12	12	12
120	CA351-100V120uF(*)G	T3510G127(*)100(**)	(*)	100V120uF	G	9.6	72.0	72.0		15	15	15
150	CA351-100V150uF(*)H	T3510H157(*)100(**)	(*)	100V150uF	H	12.0	90.0	90.0		20	20	20
220	CA351-100V220uF(*)H	T3510H227(*)100(**)	(*)	100V220uF	H	17.6	132.0	132.0		20	20	20
125 Volt 额定电压 +85℃时 (75 Volt 额定电压 +125℃时)												
1	CA351-125V1uF(*)A	T3510A105(*)125(**)	(*)	125V1uF	A	1	6	6		6	6	6
1.5	CA351-125V1.5uF(*)A	T3510A155(*)125(**)	(*)	125V1.5uF	A	1	6	6		6	6	6
2.2	CA351-125V2.2uF(*)A	T3510A225(*)125(**)	(*)	125V2.2uF	A	1	6	6		6	6	6
3.3	CA351-125V3.3uF(*)A	T3510A335(*)125(**)	(*)	125V3.3uF	A	1	6	6		6	6	6
4.7	CA351-125V4.7uF(*)B	T3510B475(*)125(**)	(*)	125V4.7uF	B	1	6	6		6	6	6
6.8	CA351-125V6.8uF(*)B	T3510B685(*)125(**)	(*)	125V6.8uF	B	1	6	6		8	8	8
10	CA351-125V10uF(*)C	T3510C106(*)125(**)	(*)	125V10uF	C	1.0	7.5	7.5		9	9	9
15	CA351-125V15uF(*)C	T3510C156(*)125(**)	(*)	125V15uF	C	1.5	11.3	11.3		9	9	9
18	CA351-125V18uF(*)D	T3510D186(*)125(**)	(*)	125V18uF	D	1.8	13.5	13.5		9	9	9
22	CA351-125V22uF(*)D	T3510D226(*)125(**)	(*)	125V22uF	D	2.2	16.5	16.5		9	9	9
27	CA351-125V27uF(*)E	T3510E276(*)125(**)	(*)	125V27uF	E	2.7	20.3	20.3		10	10	10
33	CA351-125V33uF(*)E	T3510E336(*)125(**)	(*)	125V33uF	E	3.3	24.8	24.8		10	10	10
47	CA351-125V47uF(*)F	T3510F476(*)125(**)	(*)	125V47uF	F	4.7	35.3	35.3		10	10	10
56	CA351-125V56uF(*)G	T3510G566(*)125(**)	(*)	125V56uF	G	5.6	42.0	42.0		12	12	12
68	CA351-125V68uF(*)G	T3510G686(*)125(**)	(*)	125V68uF	G	6.8	51.0	51.0		12	12	12
82	CA351-125V82uF(*)H	T3510H826(*)125(**)	(*)	125V82uF	H	8.2	61.5	61.5		15	15	15
100	CA351-125V100uF(*)H	T3510H107(*)125(**)	(*)	125V100uF	H	10.0	75.0	75.0		20	20	20

(*)：电容量允许偏差：±10%，±20%

如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。