

| 容量<br>(uF)                                  | 聚电料号                 | ADMAT料号             | 容量偏<br>差 | 规格         | 壳号 | 漏电流<br>+25℃(uA) | 漏电流<br>+85℃(uA) | 漏电流<br>+125℃(uA) | 损耗角正切<br>-55℃<br>120Hz(%) | 损耗角正切<br>+25℃<br>120Hz(%) | 损耗角正切<br>+85℃<br>120Hz(%) | 损耗角正切<br>+125℃<br>120Hz(%) |
|---------------------------------------------|----------------------|---------------------|----------|------------|----|-----------------|-----------------|------------------|---------------------------|---------------------------|---------------------------|----------------------------|
| 6.3 Volt 额定电压 +85℃时 ( 4 Volt 额定电压 +125℃时 )  |                      |                     |          |            |    |                 |                 |                  |                           |                           |                           |                            |
| 6.8                                         | CA44A-6.3V6.8uF(*)A  | T44A0A685(*)006(**) | (*)      | 6.3V6.8uF  | A  | 0.5             | 4.0             | 5.0              | 6                         | 5                         | 5                         | 6                          |
| 10                                          | CA44A-6.3V10uF(*)A   | T44A0A106(*)006(**) | (*)      | 6.3V10uF   | A  | 0.6             | 4.8             | 6.0              | 6                         | 5                         | 5                         | 6                          |
| 15                                          | CA44A-6.3V15uF(*)A   | T44A0A156(*)006(**) | (*)      | 6.3V15uF   | A  | 0.9             | 7.2             | 9.0              | 6                         | 5                         | 5                         | 6                          |
| 22                                          | CA44A-6.3V22uF(*)A   | T44A0A226(*)006(**) | (*)      | 6.3V22uF   | A  | 1.4             | 11.2            | 14.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                          | CA44A-6.3V33uF(*)A   | T44A0A336(*)006(**) | (*)      | 6.3V33uF   | A  | 2               | 16.0            | 20.0             | 6                         | 5                         | 5                         | 6                          |
| 47                                          | CA44A-6.3V47uF(*)B   | T44A0B476(*)006(**) | (*)      | 6.3V47uF   | B  | 2.9             | 23.2            | 29.0             | 6                         | 5                         | 5                         | 6                          |
| 47                                          | CA44A-6.3V47uF(*)A   | T44A0A476(*)006(**) | (*)      | 6.3V47uF   | A  | 2.9             | 23.2            | 29.0             | 6                         | 5                         | 5                         | 6                          |
| 68                                          | CA44A-6.3V68uF(*)B   | T44A0B686(*)006(**) | (*)      | 6.3V68uF   | B  | 4.3             | 34.3            | 42.8             | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-6.3V100uF(*)B  | T44A0B107(*)006(**) | (*)      | 6.3V100uF  | B  | 6.3             | 50.4            | 63.0             | 6                         | 5                         | 5                         | 6                          |
| 150                                         | CA44A-6.3V150uF(*)C  | T44A0C157(*)006(**) | (*)      | 6.3V150uF  | C  | 9.5             | 75.6            | 94.5             | 8                         | 7                         | 7                         | 8                          |
| 220                                         | CA44A-6.3V220uF(*)C  | T44A0C227(*)006(**) | (*)      | 6.3V220uF  | C  | 13.9            | 110.9           | 138.6            | 8                         | 7                         | 7                         | 8                          |
| 330                                         | CA44A-6.3V330uF(*)D  | T44A0D337(*)006(**) | (*)      | 6.3V330uF  | D  | 20.8            | 166.3           | 207.9            | 8                         | 7                         | 7                         | 8                          |
| 330                                         | CA44A-6.3V330uF(*)C  | T44A0C337(*)006(**) | (*)      | 6.3V330uF  | C  | 20.8            | 166.3           | 207.9            | 8                         | 7                         | 7                         | 8                          |
| 470                                         | CA44A-6.3V470uF(*)D  | T44A0D477(*)006(**) | (*)      | 6.3V470uF  | D  | 29.6            | 236.9           | 296.1            | 10                        | 10                        | 10                        | 10                         |
| 470                                         | CA44A-6.3V470uF(*)C  | T44A0C477(*)006(**) | (*)      | 6.3V470uF  | C  | 29.6            | 236.9           | 296.1            | 10                        | 10                        | 10                        | 10                         |
| 680                                         | CA44A-6.3V680uF(*)D  | T44A0D687(*)006(**) | (*)      | 6.3V680uF  | D  | 42.8            | 342.7           | 428.4            | 10                        | 10                        | 10                        | 10                         |
| 680                                         | CA44A-6.3V680uF(*)C  | T44A0C687(*)006(**) | (*)      | 6.3V680uF  | C  | 42.8            | 342.7           | 428.4            | 10                        | 10                        | 10                        | 10                         |
| 1000                                        | CA44A-6.3V1000uF(*)D | T44A0D108(*)006(**) | (*)      | 6.3V1000uF | D  | 63.0            | 504.0           | 630.0            | 15                        | 12                        | 15                        | 15                         |
| 10 Volt 额定电压 +85℃时 ( 6.3 Volt 额定电压 +125℃时 ) |                      |                     |          |            |    |                 |                 |                  |                           |                           |                           |                            |
| 4.7                                         | CA44A-10V4.7uF(*)A   | T44A0A475(*)010(**) | (*)      | 10V4.7uF   | A  | 0.5             | 3.8             | 4.7              | 6                         | 5                         | 5                         | 6                          |
| 6.8                                         | CA44A-10V6.8uF(*)A   | T44A0A685(*)010(**) | (*)      | 10V6.8uF   | A  | 0.7             | 5.4             | 6.8              | 6                         | 5                         | 5                         | 6                          |
| 10                                          | CA44A-10V10uF(*)A    | T44A0A106(*)010(**) | (*)      | 10V10uF    | A  | 1.0             | 8.0             | 10.0             | 6                         | 5                         | 5                         | 6                          |
| 15                                          | CA44A-10V15uF(*)A    | T44A0A156(*)010(**) | (*)      | 10V15uF    | A  | 1.5             | 12.0            | 15.0             | 6                         | 5                         | 5                         | 6                          |
| 22                                          | CA44A-10V22uF(*)A    | T44A0A226(*)010(**) | (*)      | 10V22uF    | A  | 2.2             | 17.6            | 22.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                          | CA44A-10V33uF(*)B    | T44A0B336(*)010(**) | (*)      | 10V33uF    | B  | 3.3             | 26.4            | 33.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                          | CA44A-10V33uF(*)A    | T44A0A336(*)010(**) | (*)      | 10V33uF    | A  | 3.3             | 26.4            | 33.0             | 6                         | 5                         | 5                         | 6                          |
| 47                                          | CA44A-10V47uF(*)B    | T44A0B476(*)010(**) | (*)      | 10V47uF    | B  | 4.7             | 37.6            | 47.0             | 6                         | 5                         | 5                         | 6                          |
| 68                                          | CA44A-10V68uF(*)B    | T44A0B686(*)010(**) | (*)      | 10V68uF    | B  | 6.8             | 54.4            | 68.0             | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-10V100uF(*)C   | T44A0C107(*)010(**) | (*)      | 10V100uF   | C  | 10.0            | 80.0            | 100.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-10V100uF(*)B   | T44A0B107(*)010(**) | (*)      | 10V100uF   | B  | 10.0            | 80.0            | 100.0            | 6                         | 5                         | 5                         | 6                          |
| 150                                         | CA44A-10V150uF(*)C   | T44A0C157(*)010(**) | (*)      | 10V150uF   | C  | 15.0            | 120.0           | 150.0            | 8                         | 7                         | 7                         | 8                          |
| 220                                         | CA44A-10V220uF(*)D   | T44A0D227(*)010(**) | (*)      | 10V220uF   | D  | 22.0            | 176.0           | 220.0            | 8                         | 7                         | 7                         | 8                          |
| 220                                         | CA44A-10V220uF(*)C   | T44A0C227(*)010(**) | (*)      | 10V220uF   | C  | 22.0            | 176.0           | 220.0            | 8                         | 7                         | 7                         | 8                          |
| 330                                         | CA44A-10V330uF(*)D   | T44A0D337(*)010(**) | (*)      | 10V330uF   | D  | 33.0            | 264.0           | 330.0            | 8                         | 7                         | 7                         | 8                          |
| 330                                         | CA44A-10V330uF(*)C   | T44A0C337(*)010(**) | (*)      | 10V330uF   | C  | 33.0            | 264.0           | 330.0            | 8                         | 7                         | 7                         | 8                          |
| 470                                         | CA44A-10V470uF(*)D   | T44A0D477(*)010(**) | (*)      | 10V470uF   | D  | 47.0            | 376.0           | 470.0            | 10                        | 10                        | 10                        | 10                         |
| 470                                         | CA44A-10V470uF(*)C   | T44A0C477(*)010(**) | (*)      | 10V470uF   | C  | 47.0            | 376.0           | 470.0            | 10                        | 10                        | 10                        | 10                         |
| 680                                         | CA44A-10V680uF(*)D   | T44A0D687(*)010(**) | (*)      | 10V680uF   | D  | 68.0            | 544.0           | 680.0            | 10                        | 10                        | 10                        | 10                         |
| 1000                                        | CA44A-10V1000uF(*)D  | T44A0D108(*)010(**) | (*)      | 10V1000uF  | D  | 100.0           | 800.0           | 1000.0           | 15                        | 12                        | 15                        | 15                         |
| 16 Volt 额定电压 +85℃时 ( 10 Volt 额定电压 +125℃时 )  |                      |                     |          |            |    |                 |                 |                  |                           |                           |                           |                            |
| 3.3                                         | CA44A-16V3.3uF(*)A   | T44A0A335(*)016(**) | (*)      | 16V3.3uF   | A  | 0.5             | 4.2             | 5.3              | 6                         | 5                         | 5                         | 6                          |
| 4.7                                         | CA44A-16V4.7uF(*)A   | T44A0A475(*)016(**) | (*)      | 16V4.7uF   | A  | 0.8             | 6.0             | 7.5              | 6                         | 5                         | 5                         | 6                          |
| 6.8                                         | CA44A-16V6.8uF(*)A   | T44A0A685(*)016(**) | (*)      | 16V6.8uF   | A  | 1.1             | 8.7             | 10.9             | 6                         | 5                         | 5                         | 6                          |
| 10                                          | CA44A-16V10uF(*)A    | T44A0A106(*)016(**) | (*)      | 16V10uF    | A  | 1.6             | 12.8            | 16.0             | 6                         | 5                         | 5                         | 6                          |
| 15                                          | CA44A-16V15uF(*)A    | T44A0A156(*)016(**) | (*)      | 16V15uF    | A  | 2.4             | 19.2            | 24.0             | 6                         | 5                         | 5                         | 6                          |
| 22                                          | CA44A-16V22uF(*)B    | T44A0B226(*)016(**) | (*)      | 16V22uF    | B  | 3.5             | 28.2            | 35.2             | 6                         | 5                         | 5                         | 6                          |
| 33                                          | CA44A-16V33uF(*)C    | T44A0C336(*)016(**) | (*)      | 16V33uF    | C  | 5.3             | 42.2            | 52.8             | 6                         | 5                         | 5                         | 6                          |
| 33                                          | CA44A-16V33uF(*)B    | T44A0B336(*)016(**) | (*)      | 16V33uF    | B  | 5.3             | 42.2            | 52.8             | 6                         | 5                         | 5                         | 6                          |
| 47                                          | CA44A-16V47uF(*)C    | T44A0C476(*)016(**) | (*)      | 16V47uF    | C  | 7.5             | 60.2            | 75.2             | 6                         | 5                         | 5                         | 6                          |
| 47                                          | CA44A-16V47uF(*)B    | T44A0B476(*)016(**) | (*)      | 16V47uF    | B  | 7.5             | 60.2            | 75.2             | 6                         | 5                         | 5                         | 6                          |
| 68                                          | CA44A-16V68uF(*)C    | T44A0C686(*)016(**) | (*)      | 16V68uF    | C  | 10.9            | 87.0            | 108.8            | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-16V100uF(*)D   | T44A0D107(*)016(**) | (*)      | 16V100uF   | D  | 16.0            | 128.0           | 160.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-16V100uF(*)C   | T44A0C107(*)016(**) | (*)      | 16V100uF   | C  | 16.0            | 128.0           | 160.0            | 6                         | 5                         | 5                         | 6                          |
| 150                                         | CA44A-16V150uF(*)D   | T44A0D157(*)016(**) | (*)      | 16V150uF   | D  | 24.0            | 192.0           | 240.0            | 8                         | 7                         | 7                         | 8                          |
| 150                                         | CA44A-16V150uF(*)C   | T44A0C157(*)016(**) | (*)      | 16V150uF   | C  | 24.0            | 192.0           | 240.0            | 8                         | 7                         | 7                         | 8                          |
| 220                                         | CA44A-16V220uF(*)D   | T44A0D227(*)016(**) | (*)      | 16V220uF   | D  | 35.2            | 281.6           | 352.0            | 8                         | 7                         | 7                         | 8                          |
| 220                                         | CA44A-16V220uF(*)C   | T44A0C227(*)016(**) | (*)      | 16V220uF   | C  | 35.2            | 281.6           | 352.0            | 8                         | 7                         | 7                         | 8                          |
| 330                                         | CA44A-16V330uF(*)D   | T44A0D337(*)016(**) | (*)      | 16V330uF   | D  | 52.8            | 422.4           | 528.0            | 8                         | 7                         | 7                         | 8                          |
| 470                                         | CA44A-16V470uF(*)D   | T44A0D477(*)016(**) | (*)      | 16V470uF   | D  | 75.2            | 601.6           | 752.0            | 10                        | 10                        | 10                        | 10                         |
| 20 Volt 额定电压 +85℃时 ( 13 Volt 额定电压 +125℃时 )  |                      |                     |          |            |    |                 |                 |                  |                           |                           |                           |                            |
| 2.2                                         | CA44A-20V2.2uF(*)A   | T44A0A225(*)020(**) | (*)      | 20V2.2uF   | A  | 0.4             | 3.5             | 4.4              | 6                         | 3                         | 5                         | 6                          |
| 3.3                                         | CA44A-20V3.3uF(*)A   | T44A0A335(*)020(**) | (*)      | 20V3.3uF   | A  | 0.7             | 5.3             | 6.6              | 6                         | 5                         | 5                         | 6                          |
| 4.7                                         | CA44A-20V4.7uF(*)A   | T44A0A475(*)020(**) | (*)      | 20V4.7uF   | A  | 0.9             | 7.5             | 9.4              | 6                         | 5                         | 5                         | 6                          |
| 6.8                                         | CA44A-20V6.8uF(*)A   | T44A0A685(*)020(**) | (*)      | 20V6.8uF   | A  | 1.4             | 10.9            | 13.6             | 6                         | 5                         | 5                         | 6                          |
| 10                                          | CA44A-20V10uF(*)A    | T44A0A106(*)020(**) | (*)      | 20V10uF    | A  | 2.0             | 16.0            | 20.0             | 6                         | 5                         | 5                         | 6                          |
| 15                                          | CA44A-20V15uF(*)B    | T44A0B156(*)020(**) | (*)      | 20V15uF    | B  | 3.0             | 24.0            | 30.0             | 6                         | 5                         | 5                         | 6                          |
| 22                                          | CA44A-20V22uF(*)B    | T44A0B226(*)020(**) | (*)      | 20V22uF    | B  | 4.4             | 35.2            | 44.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                          | CA44A-20V33uF(*)B    | T44A0B336(*)020(**) | (*)      | 20V33uF    | B  | 6.6             | 52.8            | 66.0             | 6                         | 5                         | 5                         | 6                          |
| 47                                          | CA44A-20V47uF(*)C    | T44A0C476(*)020(**) | (*)      | 20V47uF    | C  | 9.4             | 75.2            | 94.0             | 6                         | 5                         | 5                         | 6                          |
| 68                                          | CA44A-20V68uF(*)D    | T44A0D686(*)020(**) | (*)      | 20V68uF    | D  | 13.6            | 108.8           | 136.0            | 6                         | 5                         | 5                         | 6                          |
| 68                                          | CA44A-20V68uF(*)C    | T44A0C686(*)020(**) | (*)      | 20V68uF    | C  | 13.6            | 108.8           | 136.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-20V100uF(*)D   | T44A0D107(*)020(**) | (*)      | 20V100uF   | D  | 20.0            | 160.0           | 200.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                         | CA44A-20V100uF(*)C   | T44A0C107(*)020(**) | (*)      | 20V100uF   | C  | 20.0            | 160.0           | 200.0            | 6                         | 5                         | 5                         | 6                          |

| 容量<br>(uF)                                 | 聚电料号                | ADMAT料号             | 容量偏差 | 规格        | 壳号 | 漏电流<br>+25℃(uA) | 漏电流<br>+85℃(uA) | 漏电流<br>+125℃(uA) | 损耗角正切<br>-55℃<br>120Hz(%) | 损耗角正切<br>+25℃<br>120Hz(%) | 损耗角正切<br>+85℃<br>120Hz(%) | 损耗角正切<br>+125℃<br>120Hz(%) |
|--------------------------------------------|---------------------|---------------------|------|-----------|----|-----------------|-----------------|------------------|---------------------------|---------------------------|---------------------------|----------------------------|
| 150                                        | CA44A-20V150uF(*)D  | T44A0D157(*)020(**) | (*)  | 20V150uF  | D  | 30.0            | 240.0           | 300.0            | 8                         | 7                         | 7                         | 8                          |
| 150                                        | CA44A-20V150uF(*)C  | T44A0C157(*)020(**) | (*)  | 20V150uF  | C  | 30.0            | 240.0           | 300.0            | 8                         | 7                         | 7                         | 8                          |
| 220                                        | CA44A-20V220uF(*)D  | T44A0D227(*)020(**) | (*)  | 20V220uF  | D  | 44.0            | 352.0           | 440.0            | 8                         | 7                         | 7                         | 8                          |
| 25 Volt 额定电压 +85℃时 ( 16 Volt 额定电压 +125℃时 ) |                     |                     |      |           |    |                 |                 |                  |                           |                           |                           |                            |
| 1.5                                        | CA44A-25V1.5uF(*)A  | T44A0A155(*)025(**) | (*)  | 25V1.5uF  | A  | 0.4             | 3.0             | 3.8              | 6                         | 3                         | 5                         | 6                          |
| 2.2                                        | CA44A-25V2.2uF(*)A  | T44A0A225(*)025(**) | (*)  | 25V2.2uF  | A  | 0.6             | 4.4             | 5.5              | 6                         | 3                         | 5                         | 6                          |
| 3.3                                        | CA44A-25V3.3uF(*)A  | T44A0A335(*)025(**) | (*)  | 25V3.3uF  | A  | 0.8             | 6.6             | 8.3              | 6                         | 5                         | 5                         | 6                          |
| 4.7                                        | CA44A-25V4.7uF(*)A  | T44A0A475(*)025(**) | (*)  | 25V4.7uF  | A  | 1.2             | 9.4             | 11.8             | 6                         | 5                         | 5                         | 6                          |
| 6.8                                        | CA44A-25V6.8uF(*)A  | T44A0A685(*)025(**) | (*)  | 25V6.8uF  | A  | 1.7             | 13.6            | 17.0             | 6                         | 5                         | 5                         | 6                          |
| 10                                         | CA44A-25V10uF(*)B   | T44A0B106(*)025(**) | (*)  | 25V10uF   | B  | 2.5             | 20.0            | 25.0             | 6                         | 5                         | 5                         | 6                          |
| 15                                         | CA44A-25V15uF(*)C   | T44A0C156(*)025(**) | (*)  | 25V15uF   | C  | 3.8             | 30.0            | 37.5             | 6                         | 5                         | 5                         | 6                          |
| 15                                         | CA44A-25V15uF(*)B   | T44A0B156(*)025(**) | (*)  | 25V15uF   | B  | 3.8             | 30.0            | 37.5             | 6                         | 5                         | 5                         | 6                          |
| 22                                         | CA44A-25V22uF(*)C   | T44A0C226(*)025(**) | (*)  | 25V22uF   | C  | 5.5             | 44.0            | 55.0             | 6                         | 5                         | 5                         | 6                          |
| 22                                         | CA44A-25V22uF(*)B   | T44A0B226(*)025(**) | (*)  | 25V22uF   | B  | 5.5             | 44.0            | 55.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                         | CA44A-25V33uF(*)C   | T44A0C336(*)025(**) | (*)  | 25V33uF   | C  | 8.3             | 66.0            | 82.5             | 6                         | 5                         | 5                         | 6                          |
| 47                                         | CA44A-25V47uF(*)D   | T44A0D476(*)025(**) | (*)  | 25V47uF   | D  | 11.8            | 94.0            | 117.5            | 6                         | 5                         | 5                         | 6                          |
| 47                                         | CA44A-25V47uF(*)C   | T44A0C476(*)025(**) | (*)  | 25V47uF   | C  | 11.8            | 94.0            | 117.5            | 6                         | 5                         | 5                         | 6                          |
| 68                                         | CA44A-25V68uF(*)D   | T44A0D686(*)025(**) | (*)  | 25V68uF   | D  | 17.0            | 136.0           | 170.0            | 6                         | 5                         | 5                         | 6                          |
| 68                                         | CA44A-25V68uF(*)C   | T44A0C686(*)025(**) | (*)  | 25V68uF   | C  | 17.0            | 136.0           | 170.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                        | CA44A-25V100uF(*)D  | T44A0D107(*)025(**) | (*)  | 25V100uF  | D  | 25.0            | 200.0           | 250.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                        | CA44A-25V100uF(*)C  | T44A0C107(*)025(**) | (*)  | 25V100uF  | C  | 25.0            | 200.0           | 250.0            | 6                         | 5                         | 5                         | 6                          |
| 150                                        | CA44A-25V150uF(*)D  | T44A0D157(*)025(**) | (*)  | 25V150uF  | D  | 37.5            | 300.0           | 375.0            | 8                         | 7                         | 7                         | 8                          |
| 35 Volt 额定电压 +85℃时 ( 20 Volt 额定电压 +125℃时 ) |                     |                     |      |           |    |                 |                 |                  |                           |                           |                           |                            |
| 0.1                                        | CA44A-35V0.1uF(*)A  | T44A0A104(*)035(**) | (*)  | 35V0.1uF  | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.15                                       | CA44A-35V0.15uF(*)A | T44A0A154(*)035(**) | (*)  | 35V0.15uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.22                                       | CA44A-35V0.22uF(*)A | T44A0A224(*)035(**) | (*)  | 35V0.22uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.33                                       | CA44A-35V0.33uF(*)A | T44A0A334(*)035(**) | (*)  | 35V0.33uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.47                                       | CA44A-35V0.47uF(*)A | T44A0A474(*)035(**) | (*)  | 35V0.47uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.68                                       | CA44A-35V0.68uF(*)A | T44A0A684(*)035(**) | (*)  | 35V0.68uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 1                                          | CA44A-35V1uF(*)A    | T44A0A105(*)035(**) | (*)  | 35V1uF    | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 1.5                                        | CA44A-35V1.5uF(*)B  | T44A0B155(*)035(**) | (*)  | 35V1.5uF  | B  | 0.5             | 4.2             | 5.3              | 6                         | 3                         | 5                         | 6                          |
| 2.2                                        | CA44A-35V2.2uF(*)B  | T44A0B225(*)035(**) | (*)  | 35V2.2uF  | B  | 0.8             | 6.2             | 7.7              | 6                         | 3                         | 5                         | 6                          |
| 3.3                                        | CA44A-35V3.3uF(*)B  | T44A0B335(*)035(**) | (*)  | 35V3.3uF  | B  | 1.2             | 9.2             | 11.6             | 6                         | 5                         | 5                         | 6                          |
| 4.7                                        | CA44A-35V4.7uF(*)B  | T44A0B475(*)035(**) | (*)  | 35V4.7uF  | B  | 1.6             | 13.2            | 16.5             | 6                         | 5                         | 5                         | 6                          |
| 6.8                                        | CA44A-35V6.8uF(*)B  | T44A0B685(*)035(**) | (*)  | 35V6.8uF  | B  | 2.4             | 19.0            | 23.8             | 6                         | 5                         | 5                         | 6                          |
| 10                                         | CA44A-35V10uF(*)C   | T44A0C106(*)035(**) | (*)  | 35V10uF   | C  | 3.5             | 28.0            | 35.0             | 6                         | 5                         | 5                         | 6                          |
| 10                                         | CA44A-35V10uF(*)B   | T44A0B106(*)035(**) | (*)  | 35V10uF   | B  | 3.5             | 28.0            | 35.0             | 6                         | 5                         | 5                         | 6                          |
| 15                                         | CA44A-35V15uF(*)C   | T44A0C156(*)035(**) | (*)  | 35V15uF   | C  | 5.3             | 42.0            | 52.5             | 6                         | 5                         | 5                         | 6                          |
| 15                                         | CA44A-35V15uF(*)B   | T44A0B156(*)035(**) | (*)  | 35V15uF   | B  | 5.3             | 42.0            | 52.5             | 6                         | 5                         | 5                         | 6                          |
| 22                                         | CA44A-35V22uF(*)C   | T44A0C226(*)035(**) | (*)  | 35V22uF   | C  | 7.7             | 61.6            | 77.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                         | CA44A-35V33uF(*)D   | T44A0D336(*)035(**) | (*)  | 35V33uF   | D  | 11.6            | 92.4            | 115.5            | 6                         | 5                         | 5                         | 6                          |
| 33                                         | CA44A-35V33uF(*)C   | T44A0C336(*)035(**) | (*)  | 35V33uF   | C  | 11.6            | 92.4            | 115.5            | 6                         | 5                         | 5                         | 6                          |
| 47                                         | CA44A-35V47uF(*)D   | T44A0D476(*)035(**) | (*)  | 35V47uF   | D  | 16.5            | 131.6           | 164.5            | 6                         | 5                         | 5                         | 6                          |
| 47                                         | CA44A-35V47uF(*)C   | T44A0C476(*)035(**) | (*)  | 35V47uF   | C  | 16.5            | 131.6           | 164.5            | 6                         | 5                         | 5                         | 6                          |
| 68                                         | CA44A-35V68uF(*)D   | T44A0D686(*)035(**) | (*)  | 35V68uF   | D  | 23.8            | 190.4           | 238.0            | 6                         | 5                         | 5                         | 6                          |
| 100                                        | CA44A-35V100uF(*)D  | T44A0D107(*)035(**) | (*)  | 35V100uF  | D  | 35.0            | 280.0           | 350.0            | 6                         | 5                         | 5                         | 6                          |
| 40 Volt 额定电压 +85℃时 ( 25 Volt 额定电压 +125℃时 ) |                     |                     |      |           |    |                 |                 |                  |                           |                           |                           |                            |
| 0.1                                        | CA44A-40V0.1uF(*)A  | T44A0A104(*)040(**) | (*)  | 40V0.1uF  | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.15                                       | CA44A-40V0.15uF(*)A | T44A0A154(*)040(**) | (*)  | 40V0.15uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.22                                       | CA44A-40V0.22uF(*)A | T44A0A224(*)040(**) | (*)  | 40V0.22uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.33                                       | CA44A-40V0.33uF(*)A | T44A0A334(*)040(**) | (*)  | 40V0.33uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.47                                       | CA44A-40V0.47uF(*)A | T44A0A474(*)040(**) | (*)  | 40V0.47uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.68                                       | CA44A-40V0.68uF(*)A | T44A0A684(*)040(**) | (*)  | 40V0.68uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 1                                          | CA44A-40V1uF(*)A    | T44A0A105(*)040(**) | (*)  | 40V1uF    | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 1.5                                        | CA44A-40V1.5uF(*)B  | T44A0B155(*)040(**) | (*)  | 40V1.5uF  | B  | 0.6             | 4.8             | 6.0              | 6                         | 3                         | 5                         | 6                          |
| 2.2                                        | CA44A-40V2.2uF(*)B  | T44A0B225(*)040(**) | (*)  | 40V2.2uF  | B  | 0.9             | 7.0             | 8.8              | 6                         | 3                         | 5                         | 6                          |
| 3.3                                        | CA44A-40V3.3uF(*)B  | T44A0B335(*)040(**) | (*)  | 40V3.3uF  | B  | 1.3             | 10.6            | 13.2             | 6                         | 5                         | 5                         | 6                          |
| 4.7                                        | CA44A-40V4.7uF(*)B  | T44A0B475(*)040(**) | (*)  | 40V4.7uF  | B  | 1.9             | 15.0            | 18.8             | 6                         | 5                         | 5                         | 6                          |
| 6.8                                        | CA44A-40V6.8uF(*)B  | T44A0B685(*)040(**) | (*)  | 40V6.8uF  | B  | 2.7             | 21.8            | 27.2             | 6                         | 5                         | 5                         | 6                          |
| 10                                         | CA44A-40V10uF(*)C   | T44A0C106(*)040(**) | (*)  | 40V10uF   | C  | 4.0             | 32.0            | 40.0             | 6                         | 5                         | 5                         | 6                          |
| 15                                         | CA44A-40V15uF(*)C   | T44A0C156(*)040(**) | (*)  | 40V15uF   | C  | 6.0             | 48.0            | 60.0             | 6                         | 5                         | 5                         | 6                          |
| 22                                         | CA44A-40V22uF(*)C   | T44A0C226(*)040(**) | (*)  | 40V22uF   | C  | 8.8             | 70.4            | 88.0             | 6                         | 5                         | 5                         | 6                          |
| 33                                         | CA44A-40V33uF(*)D   | T44A0D336(*)040(**) | (*)  | 40V33uF   | D  | 13.2            | 105.6           | 132.0            | 6                         | 5                         | 5                         | 6                          |
| 47                                         | CA44A-40V47uF(*)D   | T44A0D476(*)040(**) | (*)  | 40V47uF   | D  | 18.8            | 150.4           | 188.0            | 6                         | 5                         | 5                         | 6                          |
| 63 Volt 额定电压 +85℃时 ( 40 Volt 额定电压 +125℃时 ) |                     |                     |      |           |    |                 |                 |                  |                           |                           |                           |                            |
| 0.1                                        | CA44A-50V0.1uF(*)A  | T44A0A104(*)050(**) | (*)  | 50V0.1uF  | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.15                                       | CA44A-50V0.15uF(*)A | T44A0A154(*)050(**) | (*)  | 50V0.15uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.22                                       | CA44A-50V0.22uF(*)A | T44A0A224(*)050(**) | (*)  | 50V0.22uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.33                                       | CA44A-50V0.33uF(*)A | T44A0A334(*)050(**) | (*)  | 50V0.33uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.47                                       | CA44A-50V0.47uF(*)A | T44A0A474(*)050(**) | (*)  | 50V0.47uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 0.68                                       | CA44A-50V0.68uF(*)A | T44A0A684(*)050(**) | (*)  | 50V0.68uF | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 1                                          | CA44A-50V1uF(*)A    | T44A0A105(*)050(**) | (*)  | 50V1uF    | A  | 0.5             | 4.0             | 5.0              | 6                         | 3                         | 5                         | 6                          |
| 1.5                                        | CA44A-50V1.5uF(*)B  | T44A0B155(*)050(**) | (*)  | 50V1.5uF  | B  | 0.8             | 6.0             | 7.5              | 6                         | 3                         | 5                         | 6                          |
| 2.2                                        | CA44A-50V2.2uF(*)B  | T44A0B225(*)050(**) | (*)  | 50V2.2uF  | B  | 1.1             | 8.8             | 11.0             | 6                         | 3                         | 5                         | 6                          |



CA44A 系列

| 容量<br>(uF) | 聚电料号               | ADMAT料号             | 容量偏<br>差 | 规格       | 壳号 | 漏电流<br>+25℃(uA) | 漏电流<br>+85℃(uA) | 漏电流<br>+125℃(uA) | 损耗角正切<br>-55℃<br>120Hz(%) | 损耗角正切<br>+25℃<br>120Hz(%) | 损耗角正切<br>+85℃<br>120Hz(%) | 损耗角正切<br>+125℃<br>120Hz(%) |
|------------|--------------------|---------------------|----------|----------|----|-----------------|-----------------|------------------|---------------------------|---------------------------|---------------------------|----------------------------|
| 3.3        | CA44A-50V3.3uF(*)B | T44A0B335(*)050(**) | (*)      | 50V3.3uF | B  | 1.7             | 13.2            | 16.5             | 6                         | 5                         | 5                         | 6                          |
| 4.7        | CA44A-50V4.7uF(*)B | T44A0B475(*)050(**) | (*)      | 50V4.7uF | B  | 2.4             | 18.8            | 23.5             | 6                         | 5                         | 5                         | 6                          |
| 6.8        | CA44A-50V6.8uF(*)C | T44A0C685(*)050(**) | (*)      | 50V6.8uF | C  | 3.4             | 27.2            | 34.0             | 6                         | 5                         | 5                         | 6                          |
| 10         | CA44A-50V10uF(*)C  | T44A0C106(*)050(**) | (*)      | 50V10uF  | C  | 5.0             | 40.0            | 50.0             | 6                         | 5                         | 5                         | 6                          |
| 15         | CA44A-50V15uF(*)C  | T44A0C156(*)050(**) | (*)      | 50V15uF  | C  | 7.5             | 60.0            | 75.0             | 6                         | 5                         | 5                         | 6                          |
| 22         | CA44A-50V22uF(*)D  | T44A0D226(*)050(**) | (*)      | 50V22uF  | D  | 11.0            | 88.0            | 110.0            | 6                         | 5                         | 5                         | 6                          |
| 33         | CA44A-50V33uF(*)D  | T44A0D336(*)050(**) | (*)      | 50V33uF  | D  | 16.5            | 132.0           | 165.0            | 6                         | 5                         | 5                         | 6                          |

(\*)：电容量允许偏差：±10%，±20%  
如电压、容量、电容量允许偏差等有特殊要求，请与上海聚电联系。